

ProCash 280

Monofunction cash dispenser
for indoor installations



Compact design

Bundle output
of up to 60 notes

Optimized cash
management

Usage in extreme
climates

Flexible
deployment

Comprehensive
security
solutions

Open hardware
and software
architectures

Proven dispenser
technology



Technical Data

ProCash 280

ProCash 280

Monofunction cash dispenser

The ProCash 280 is the entry-level system in Wincor Nixdorf's ProCash product family. It is the ideal system for usage in extreme climates, where a robust machine type is needed, at which space is limited and the focus is on cash handling.

Featuring up to four cassettes, the ProCash 280 also guarantees maximum availability thanks to its integrated open software standards.

Using best-in-class technology, the ProCash 280 comes with high level security solutions such as a biometric reader, an Anti-Manipulation Card Slot and security surveillance solutions.

DISPLAY

- 8 softkeys
- Touchscreen
- 15" TFT LCD

KEYBOARD

- EPP PCI 2.x certified
(Remote Key Loading with V6)

CARD HANDLING

- Motorized card reader LOCO/HICO, track down magnetic read only, read/write Smart/IC card
- Motorized hybrid card reader HICO 1, 2, 3; MTD USB, magnetic read/write, read/write Smart/IC card
- Dip card reader

CASH DISPENSING

- Up to 4 cassettes
- Max. filling height per cassette: 310 mm
- Scalable cassette concept
- Note reject/bundle retract
- Withdrawals up to 60 notes in bundles

SECURITY

- Cash security:
Safe: UL 291 Level 1, C
Mechanical and electronic locks

- Data and software security:
Anti-Manipulation Card Slot
Awareness mirrors
Privacy display filter for the monitor
- Identity and access control:
Fingerprint sensor
Intelligent operator authentication via CryptA Stick
- Security surveillance:
Cash removal and portrait camera

PRINTERS

- Receipt printer (Thermal printer)
- Journal printer (Impact printer)

MARKETING FEATURES

- Illuminated logo panel
- Optical indicators (MEIs)

AUDIO

- Loudspeakers
- Headset jack

OPERATING SYSTEM

- Windows XP

ENVIRONMENTAL CONDITIONS

- Temperature range: + 5°C to + 40°C

TECHNICAL DETAILS

- Supply voltage range:
110 - 120 V; 220 - 240 V

- Mains frequency 50/60 Hz
- Uninterruptable Power Supply

INSTALLATION

- Indoors
- Standalone
- Frontload

APPROVALS

