

ProCash 281

Multifunction Automated Teller Machine
for indoor installations



Withdrawals up
to 60 notes in
bundles

Envelope deposit
capacity up to 400

Flexible
configuration
options


Small footprint

Best-in-class
dispenser
technology

Comprehensive
security
solutions

Open hardware
and software
architectures

Flexible
deployment



ProCash 281

Multifunction ATM

The ProCash 281 is a multifunction Automated Teller Machine, specially made for places requiring a small footprint.

The ProCash 281 comes with best-in-class dispenser technology, an envelope desposit and integrated open software standards.

DISPLAY

- 8 softkeys
- Touchscreen
- 15" TFT LCD

KEYBOARD

- EPP PCI 2.x certified (Remote Key Loading with V6)

CARD HANDLING

- Motorized card reader
LOCO/HICO, track down magnetic read only, read/write Smart/IC card
- Motorized hybrid card reader
HICO 1, 2, 3; MTD USB, magnetic read/write, read/write Smart/IC card
- Dip card reader

CASH DISPENSING

- Up to 4 cassettes
- Max. filling height per cassette: 310 mm
- Scalable cassette concept
- Note reject/bundle retract
- Withdrawals up to 60 notes in bundles

SECURITY

- Cash security:
Safe: UL 291 Level 1
Mechanical and electronic locks
- Data and software security:
Anti-Manipulation Card Slot

- Awareness mirrors
- Privacy display filter for the monitor
- Identity and access control:
Fingerprint sensor
Intelligent operator authentication via CryptA Stick
- Security surveillance:
Cash removal and portrait camera

PRINTERS

- Receipt printer (Thermal printer)
- Journal printer (Impact printer)
- Envelope printer
 - Wire-dot matrix printing
 - 9-dot matrix
 - Black ink color
 - Ink life approx 7,500 transactions
 - Print speed approx 1.64 sec/80 characters
 - Transaction data printed in one line, max. 80 characters

ENVELOPE DEPOSITS

- Recommended envelope size: 104.8 x 238.1 mm
- Acceptable envelope size: 95-108 x 150-244 mm
- Printable anvelope size: 95-108 x 175-244 mm
- Capacity: Up to 400 envelopes, depending on filling
- Max. thickness of filled envelopes up to 12 mm

MARKETING FEATURES

- Illuminated logo panel
- Optical indicators (MEIs)

AUDIO

- Loudspeakers
- Headset jack

OPERATING SYSTEM

- Windows XP

ENVIROMENTAL CONDITIONS

- Temperature range: + 5°C to + 40°C

TECHNICAL DETAILS

- Supply voltage range: 110 - 120 V; 220 - 240 V
- Mains frequency 50/60 Hz
- Uninterruptable Power Supply

INSTALLATION

- Indoors
- Standalone
- Frontload

APPROVALS

